## **Supported Parameters in J1708:** (Version 2.0)

- **PID 44:** Attention/Warning Indicator Lamp Status
- **PID 51:** Percent Throttle Position
- **PID 52:** Engine Intercooler Temperature
- **PID 69:** Two Speed Axle Switch Status
- **PID 70:** Parking Brake Switch Status
- **PID 84:** Wheel-Based Vehicle Speed
- **PID 91:** Percent Accelerator Pedal Position
- **PID 92:** Percent Engine Load
- **PID 94:** Fuel Delivery Pressure
- **PID 96:** Fuel Level
- **PID 98:** Engine Oil Level
- **PID 99:** Engine Oil Filter Differential Pressure
- **PID 100:** Engine Oil Pressure
- **PID 101:** Crankcase Pressure
- **PID 102:** Boost Pressure
- PID 103: Turbocharger #1 Speed
- **PID 104:** Turbo Oil Pressure
- **PID 105:** Intake Manifold Temperature
- **PID 109:** Coolant Pressure
- **PID 110:** Coolant Temperature
- **PID 111:** Coolant Level
- PID 124: Transmission Oil Level
- PID 127: Transmission Oil Pressure
- PID 158: Battery Potential (Voltage) Switched
- **PID 166:** Rated Engine Power
- **PID 168:** Battery Potential (Voltage)
- **PID 172:** Air Inlet Temperature
- **PID 173:** Exhaust Gas Temperature
- **PID 174:** Fuel Temperature
- **PID 175:** Engine Oil Temperature
- **PID 176:** Turbo Oil Temperature
- **PID 177:** Transmission #1 Oil Temperature
- PID 182: Trip Fuel
- PID 183: Instantaneous Fuel Rate
- **PID 184:** Instantaneous Fuel Economy
- **PID 185:** Average Fuel Economy
- **PID 186:** Power Takeoff Speed
- **PID 189:** Rated Engine Speed (RPM)
- **PID 190:** Engine Speed (RPM)
- PID 194: Active Diagnostic Trouble Codes \*

(\*Note: The trouble codes that are translated are limited to a select number of parameters supported by Maretron J2K100 devices)

PID 245: Total Vehicle DistancePID 247: Total Engine HoursPID 250: Total Fuel Used